



FX12D2550XF36 12.1-inch Wall Mount Panel PC

LCD Panel Specification - INTEL® Cedar Trail-D Processor D2550 (1.86GHz)	
Viewable Size Image	12.1inch
Active Display Area	246(H) x 184.5(V)
Pixel Pitch	0.3075 (H) x 0.3075 (V)
Resolution	800X3 (RGB) X600
Contrast Ratio	600:1 (typ.)
Display Color	16.2M / 262K colors
Brightness	300 cd/m2 (typ.)
Viewing Angle	-80°~80° (H); -80 ° ~80° (V)
Recommend Resolution	800x600
Power Consumption	45W typical, normal operation
Touch (Optional)	5 -wires Resistive touch
System Specification	
Form Factor	48 x 102mm 3.5" SBC Form Facto
Processor	INTEL® Cedar Trail-D Processor D2550 (1.86GHz)
System Chipset	INTEL®NM10 Express chipset
System Memory	Support 1 * DDR3 1066MHz Single CH up to 4GB (D2550)
BIOS	AMI 16MB SMT Flash ROM
LCD Support	Onboard 1 * 24-bits Dual channel & 1 * 18-bits Single LVDS connectors
Ethernet	2 * RTL8111E PCI-EVL Gigabit LAN
Audio	Realtek ALC662 HD Audio CODEC with 4-Channel
Serial	1 x RS-232, 1 x RS-232/422/485*
USB	Embedded 7 * USB 2.0/1.1
Graphics	Support DirectX 9 Graphics up to 640MHz
Storage	1 * Serial ATAll 3Gb/s connectors 1 * CFast card socket
Expansion Slots	1 * MINI PCI-E
Operating Temperature	-20 ~ 60°C

I / O Interface	4 * USB 2.0/1.1 ports 2 * RJ-45 ports 1* Line-out port 1 * DVI-I port 1 1* 12V DC-IN JACK 3* RS232 1* RS232/422/485 1* Power Key /Power LED 1* Rest Key/ HDD LED